

MICROSYSTEM CAPILLARY SEPARATIONS

Publication number: WO0193976 (A2)

Publication date: 2001-12-13

Inventor(s): TEGROTHUIS WARD E; WEGENG ROBERT S; WHYATT GREG A; STENKAMP VICTORIA S; GAUGLITZ PHILLIP A
Applicant(s): BATTELLE MEMORIAL INSTITUTE [US]

Classification:

- international: B01B1/00; B01D3/00; B01D5/00; B01D19/00; B01J19/00; C01B3/38; F28D9/00; H01M8/04; B01L3/00; B01B1/00; B01D3/00; B01D5/00; B01D19/00; B01J19/00; C01B3/00; F28D9/00; H01M8/04; B01L3/00, (IPC1-7): B01D17/00

- European: B01B1/00B; B01D3/00; B01D5/00B; B01D19/00F; B01J19/00R; C01B3/38B; F28D9/00F4B

Application number: WO2001US17622 20010530

Priority number(s): US2000058871 20000606

Also published as:

WO0193976 (A3)
 US6666909 (B1)
 AU7506901 (A)
 CA2410462 (A1)
 JP2004509733 (T)


more >>

Cited documents:

US3961918 (A)

Abstract of WO 0193976 (A2)

Laminated, multiphase separators and contactors having wicking structures and gas flow channels are described. Some preferred embodiments are combined with microchannel heat exchange. Integrated systems containing these components are also part of the present invention.



Data supplied from the **esp@cenet** database — Worldwide